5% AXIAL LEADED RESISTOR

VALUE 10 Ω

BRN BLK BLK GLD

1 0 0

POWER 250mW

IN HOUSE P/N: _____100

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 22 Ω

RED RED BLK GLD

2 2 0

POWER 250mW

IN HOUSE P/N: _____220

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 47 Ω

ORN VIO BLK GLD

4 7 0

POWER 250mW

IN HOUSE P/N: _____470

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 11 Ω

BRN BRN BLK GLD

1 1 0

POWER 250mW

IN HOUSE P/N: _____110

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 24 Ω

RED YEL BLK GLD

2 4 0

POWER 250mW

IN HOUSE P/N: _____240

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 51 Ω

GRN BRN BLK GLD

5 1 0

POWER 250mW

IN HOUSE P/N: _____510

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 12 Ω

BRN RED BLK GLD

1 2 0

POWER 250mW

IN HOUSE P/N: _____120

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 27 Ω

RED VIO BLK GLD

2 7 0

POWER 250mW

IN HOUSE P/N: _____270

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 56 Ω

GRN BLU BLK GLD

5 6 0

POWER 250mW

IN HOUSE P/N: _____560

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 13 Ω

BRN ORN BLK GLD

1 3 0

POWER 250mW

IN HOUSE P/N: _____130

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 30 Ω

ORN BLK BLK GLD

3 0 0

POWER 250mW

IN HOUSE P/N: _____300

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 62 Ω

BLU RED BLK GLD

6 2 0

POWER 250mW

IN HOUSE P/N: _____620

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 15 Ω

BRN GRN BLK GLD

1 5 0

POWER 250mW

IN HOUSE P/N: _____150

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 33 Ω

ORN ORN BLK GLD

3 3 0

POWER 250mW

IN HOUSE P/N: _____330

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 68 Ω

BLU GRY BLK GLD

6 8 0

POWER 250mW

IN HOUSE P/N: _____680

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 16 Ω

BRN BLU BLK GLD

1 6 0

POWER 250mW

IN HOUSE P/N: _____160

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 36 Ω

ORN BLU BLK GLD

3 6 0

POWER 250mW

IN HOUSE P/N: _____360

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 75 Ω

VIO GRN BRN GLD

7 5 0

POWER 250mW

IN HOUSE P/N: _____750

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 18 Ω

BRN GRY BLK GLD

1 8 0

POWER 250mW

IN HOUSE P/N: _____180

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 39 Ω

ORN WHT BLK GLD

3 9 0

POWER 250mW

IN HOUSE P/N: _____390

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 82 Ω

GRY RED BLK GLD

8 2 0

POWER 250mW

IN HOUSE P/N: _____820

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 20 Ω

RED BLK BLK GLD

2 0 0

POWER 250mW

IN HOUSE P/N: _____200

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 43 Ω

YEL ORN BLK GLD

4 3 0

POWER 250mW

IN HOUSE P/N: _____430

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VALUE 91 Ω

WHT BRN BLK GLD

9 1 0

POWER 250mW

IN HOUSE P/N: _____910

TYPE: Carbon Film

TOLERANCE ±5%

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____